



Barracuda I Model 6096 Fish Cleaning Station



Standard Features:

- Heavy-duty waste grinder
- Exclusive dual 6" inlet chute protects both your patrons and the grinder
- $\frac{3}{4}$ " Sanalite cutting boards that slope to central drainage basin
- Side-mounted, 60" x 19" x 34" high ADA-compliant cutting table
- Two Start/Stop control stations
- Automatic basin flush nozzles
- Four 60" side-mount spray hoses
- 15A/120V convenience outlet circuit with four duplex GFCI receptacles
- Welded T304 stainless steel cabinet with adjustable leveling feet
- Lockable doors and removable front panel for maintenance access
- Shipped fully assembled

Grinder Specifications:

- 2HP/230V/3PH AC motor
- 29:1 reduction gear motor
- Counter-rotating, 60 RPM shafts with hardened cutting teeth
- 6" downward waste-discharge port

Requirements:

- 30A/240VAC, 1- or 3-phase service
- 10 GPM, 50-60 PSI water supply (1" female NPT inlet valve)

Available Options:

- Lockable winter cover
- Overhead hoses and stringer hooks

Barracuda Intelligent Control System:

- Either green button starts the grinder and rinse.
- Adjustable timers automatically stop the grinder and rinse at the same time. After a brief pause, the rinse resumes long enough to flush all wastes through your drain. Your patrons can't leave the grinder or rinse water running!
- **1st Jam Release™** reverses and halts the grinder on initial contact to minimize cutter damage.
- Either red button immediately stops the grinder.
- Displays daily, weekly and monthly usage.
- Housed in NEMA 4X enclosures.

May 22, 2017



www.qualitymandm.com • sales@qualitymandm.com

4280 E 14th Street, Des Moines, Iowa 50313

(515) 266-2268 • Fax: (515) 266-0243